

# Striping Paint - Aerosol



# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol paint. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE-Pacific aerosol products.

## STRIPING PAINT

701 TRAFFIC WHITE SUPREME	730 TRAFFIC RED	770 ASPHALT BLACK
702 TRAFFIC YELLOW SUPREME	740 TRAFFIC ORANGE	780 CONCRETE GRAY
710 TRAFFIC WHITE	750 TRAFFIC BLUE	785 FLUORESCENT RED/ORANGE
720 TRAFFIC YELLOW	760 TRAFFIC GREEN	

**PRODUCT NAME:** (18A1) STRIPING PAINT - ALL COLORS **PRODUCT CODE:** 18A1 **HMIS CODES:** H 2 F 4 R 1 P X  
**PRODUCT USE:** GROUND TRAFFIC < 66% V.O.C.

## SECTION I - MANUFACTURER IDENTIFICATION

**MANUFACTURER'S NAME:** AerVOE-Pacific Company, Inc. **ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**INFORMATION PHONE:** (775) 782-0100 **EMERGENCY PHONE:** 1-800-424-9300  
**DATE REVISED:** 06-01-00 **REASON REVISED:** Updated

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*XYLENE (CAS 1330 20 7)	5	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
*ETHYL BENZENE (CAS 100 41 4)	1	100 PPM	100 PPM	N/A	3500 mg / kg RAT (ORAL)	N/A
ACETONE (CAS 67 64 1)	10	750 PPM	750 PPM		9750 mg / kg RAT (ORAL)	N/A
PETROLEUM NAPHTHA (CAS 64742 89 8)	20	400 PPM	400 PPM	N/A	>25 ml / kg RAT (ORAL)	14,000-16,000 PPM / 4 hr RAT
MINERAL SPIRITS (CAS 8052 41 3)	<5.0%	100 PPM	100 PPM		N/A	N/A
PROPANE (CAS 74 98 6)	10	1000 PPM	1000 PPM		N/A	N/A
ISOBUTANE (CAS 75 28 5)	<5.0%	800 PPM	800 PPM	ESTIMATED	N/A	520,000 PPM; 2 hr MOUSE (EXP)
NORMAL BUTANE (CAS 106 97 8)	5	600 PPM	600 PPM		N/A	658 mg / L; 4 hr RAT (INHA)

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N/A applies to not available or not applicable

**PRODUCT CODE:** 18A1

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**  
**BOILING POINT:** -10° F / -23° C **SPECIFIC GRAVITY (H20=1):** 0.9 **COEFFICIENT OF WATER/OIL DIST:** N/A  
**ODOR THRESHOLD:** N/A **VAPOR DENSITY:** Heavier than air **SOLUBILITY IN WATER:** Negligible  
**EVAPORATION RATE:** Faster than n-Butyl Acetate **APPEARANCE AND ODOR:** Opaque Liquid / Solvent Based Odor  
**COATING V.O.C. :** 5.70 lbs / Imp gal 4.75 lbs / US gal 569 gms / ltr **FREEZING POINT:** N/A **pH:** N/A

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** -22° F / -30° C **METHOD USED:** Estimated **FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 0.7% **UPPER:** 12.8%  
**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO<sub>2</sub>, Dry Chemical, Water Fog  
**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS -** Closed containers may explode due to pressure build up from extreme heat or fire. Aerosol spray is extremely flammable.  
**FLAMMABILITY - T.D.G.R. CLASS:** Consumer Commodity ORM-D, NFPA 30B, Level 2 Aerosol  
**SENSITIVITY TO IMPACT:** Do not puncture **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

## SECTION V - REACTIVITY DATA

**STABILITY:** Stable **CONDITIONS TO AVOID:** High temperatures  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

## SECTION VI - HEALTH HAZARD DATA

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.  
**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE - SKIN:** May cause irritation or burning sensation.  
**EYES:** Primary irritation.  
**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.  
**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A  
**HEALTH HAZARDS (ACUTE AND CHRONIC) - INHALATION:** Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). **SKIN OR EYE CONTACT:** Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.  
**CARCINOGENICITY:** None known **NTP?** No **IARC MONOGRAPHS?** No **OSHA REGULATED?** No  
**TERATOGENICITY - N/A** **MUTAGENICITY - N/A** **TOXICOLOGICALLY SYNERGISTIC PRODUCT - N/A**  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known  
**EMERGENCY AND FIRST AID PROCEDURES - VAPORS:** Remove from exposure and restore breathing, seek medical attention.  
**SPLASH: (SKIN)** Wash affected area, remove contaminated clothing, see physician if any irritation persists.  
**SPLASH: (EYES)** Flush immediately with water for 15 minutes and take to a physician.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition: Flames, sparks, static electricity & electrical. Ventilate area and soak up with inert absorbent using non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a **TLV of 10mg/cubic meter.**

## SECTION VIII - CONTROL MEASURES

**RESPIRATORY PROTECTION - Outdoors:** Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator.  
**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.  
**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.  
**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

## SECTION IX - DISCLAIMER

DISCLAIMER - THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.

## Striping Paint - Bulk



# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color bulk paint. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE-Pacific bulk products.

### STRIPING PAINT

710 TRAFFIC WHITE  
720 TRAFFIC YELLOW  
730 TRAFFIC RED

740 TRAFFIC  
750 TRAFFIC ORANGE  
760 TRAFFIC GREEN

770 ASPHALT BLACK  
780 CONCRETE GRAY  
785 FLUORESCENT RED/ORANGE

**PRODUCT NAME:** (18B1) STRIPING PAINT - ALL COLORS  
**PRODUCT USE:** GROUND TRAFFIC

**PRODUCT CODE:** 18B1

**HMIS CODES:** H F R P  
2 3 0 X

### SECTION I - MANUFACTURER IDENTIFICATION

**MANUFACTURER'S NAME:** AerVOE-Pacific Company, Inc.  
**INFORMATION PHONE:** (775) 782-0100  
**DATE REVISED:** 06-15-00

**ADDRESS:** 1198 Mark Circle., Gardnerville, NV 89410  
**EMERGENCY PHONE:** 1-800-424-9300  
**REASON REVISED:** Updated

### SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*XYLENE (CAS 1330 20 7)	9	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
*ETHYL BENZENE (CAS 100 41 4)	1	100 PPM	100 PPM	N/A	3500 mg / kg RAT (ORAL)	N/A
ACETONE (CAS 67 64 1)	10	750 PPM	750 PPM		9750 mg / kg RAT (ORAL)	6700 PPM / 4 hr RAT (INHA)
PETROLEUM NAPHTHA (CAS 64742 89 8)	25	400 PPM	400 PPM	N/A	>25 ml / kg RAT (ORAL)	14,000-16,000 PPM / 4 hr RAT

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N/A applies to not available or not applicable

**PRODUCT CODE:** 18B1

### SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

**BOILING POINT:** 133° to 279 ° F / 56° to 137° C  
**ODOR THRESHOLD:** N/A  
**EVAPORATION RATE:** Slower than n-Butyl Acetate  
**COATING V.O.C. :** 4.27 lbs / Imp gal

**SPECIFIC GRAVITY (H2O=1):** 1.2  
**VAPOR DENSITY:** Heavier than air  
**APPEARANCE AND ODOR:** Opaque Liquid / Solvent Based Odor

**COEFFICIENT OF WATER/OIL DIST:** N/A  
**SOLUBILITY IN WATER:** Negligible  
**FREEZING POINT:** N/A  
**pH:** N/A

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** < 73° F / 29° C  
**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog  
**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS -** Closed containers may explode due to pressure build up from extreme heat or fire.  
**FLAMMABILITY - T.D.G.R. CLASS:** Paint Related Material, Class 3, UN1263, PG II  
**SENSITIVITY TO IMPACT:** Do not puncture

**METHOD USED:** Estimated  
**FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 1.0%  
**UPPER:** 12.8%

**SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

### SECTION V - REACTIVITY DATA

**STABILITY:** Stable  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

**CONDITIONS TO AVOID:** High temperatures

### SECTION VI - HEALTH HAZARD DATA

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.  
**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE - SKIN:** May cause irritation or burning sensation.  
**EYES:** Primary irritation.  
**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.  
**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A  
**HEALTH HAZARDS (ACUTE AND CHRONIC) - INHALATION:** Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness).  
**SKIN OR EYE CONTACT:** Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.  
**CARCINOGENICITY:** None known  
**TERATOGENICITY - N/A**  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known  
**EMERGENCY AND FIRST AID PROCEDURES - VAPORS:** Remove from exposure and restore breathing, seek medical attention.  
**SPLASH: (SKIN)** Wash affected area, remove contaminated clothing, see physician if any irritation persists.  
**SPLASH: (EYES)** Flush immediately with water for 15 minutes and take to a physician.

**NTP? No**  
**MUTAGENICITY - N/A**  
**IARC MONOGRAPHS? No**  
**TOXICOLOGICALLY SYNERGISTIC PRODUCT - N/A**  
**OSHA REGULATED? No**

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition: Flames, sparks, static electricity & electrical. Ventilate area and soak up with inert absorbent using non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a **TLV of 10mg/cubic meter.**

### SECTION VIII - CONTROL MEASURES

**RESPIRATORY PROTECTION -** Outdoors: Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator.  
**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.  
**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.  
**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

### SECTION IX - DISCLAIMER

DISCLAIMER - THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.